Department of Labor & Industries WISHA Services PO Box 44650 Olympia WA 98504-4650



CRANES, DERRICKS OR MATERIAL HANDLING DEVICES WORKSHEET

Waterfront Operations

Olympia WA 98	8504-4650							•				
Rental Yes No	If yes, rental	companies name										
Name of owner					Previous App. State Cert. #			Expiration date		Wt. test exp. date		
Address				City				State ZIP+4				
Descriptions:	Derrick		Remains at	-						Owner ID	‡	
Crane	Other (desc	ribe)	Yes L	No, i	f No, explain							
Manufacturer					Model num	ber		Serial number				
Exact location						If crane or derrick, state type: Rail, Steam, Etc.						
Powered by: Supplied electric Steam Diesel Diesel electric Other						Service status at time of tests (describe) Magnet Container spreader						
		Lifting Clamshell Other Type of boom construction										
Boom length at tir					Type of boo	oni construc	tion					
Main hoist:		Vhip:	Jib:									
Wire Rope Main Hoist	No. Parts	Diameter	No. strands	Wires	per strand	Type core		Break strength	Attach manufacturer's certificate of wire rope:			
Whip									☐ Y		No	
Trolley									_			
Boom				-					Certi	ficate av	ailable	
Boom Pendants	,			-					☐ Y	es 🗆	No	
									-	CS =		
a) Durable ratir b) Boom angle c) Radius indic d) Operator cor of contro e) Main hoist w f) Whip hoists g) Travel alarm h) Gantry, trolle i) All pins and j) Counterweig k) Hydraulic sy l) Crane Struct 4. TEST REQ minimum radi	ng chart visible to dindicator ————————————————————————————————————	planation w load test for crane ermediate radii de ad 25% excess: to	es shall be base eemed necessary o 50 T - proof lo	ed on n	m) Ain n) Ele o) Ble p) All q) All r) All s) Bo t) Int u) Ca v) All w) We x) An y) Ov manufacture' te of certific	r system sectrical syste sectrical syste secks and she deadening hook safet; brakes om light fix ercom syste ble clamps, clutches, d eight indicat titi-Collision verload prev s load rati cation. A c	skeaves sheaves ng of cables fety latches & straps fixture safety lines stem dock to cab os, proper size, type spacing dogs, gauges cator in proper working order on Device revention system ating to be applied at 10% ex A derrick shall be proof load to			in exces	mum and	
in feet		Los. Attach	nment Weight		Rated Car Tons	Los.	Pe	rcentage of load tes	t	Main /V	Vhip	
Means of applicati		aby eartify the sky	ove tests and/or	avami-				oad rating - designate			urer	
	Was	hington state safet	y standards for l	ongsho	ore, stevedor	e and relat	ted wa	in accordance with terfront operation, V 296 - Chapter 304			ter 56	
Date	Address		City		ZIP+4	ZIP+4 Sig		Signature of certified inspector				